#### **WASTELOAD ANALYSIS [WLA] Addendum: Statement of Basis** SUMMARY Discharging Facility: Velvet Mine UPDES No: UT-UT0025810 0.77 cfs Current Flow: 0.50 MGD 0.77 cfs Design Flow 0.50 MGD unnamed dry wash:Big Indian Wash:Hatch Wash:Kane Creek: Colorado River Receiving Water: Stream Classification: 2B, 3C, 4 7Q10 Stream Flows [cfs]: 0.0 Summer (July-Sept) 0.0 Fall (Oct-Dec) 7Q10 0.0 Winter (Jan-Mar) 7Q10 0.0 Spring (Apr-June) 7Q10 0.0 Average 700.0 Summer (July-Sept) 80th Percentile Stream TDS Values: 700.0 Fall (Oct-Dec) 80th Percentile 700.0 Winter (Jan-Mar) 80th Percentile 700.0 Spring (Apr-June) 80th Percentile **WQ Standard: Effluent Limits:** Flow, MGD: 0.50 MGD Design Flow 5.0 Indicator BOD, mg/l: 25.0 Summer Dissolved Oxygen, mg/l 5.0 Summer 5.0 30 Day Average Varies Function of pH and Temperature 8.2 Summer TNH3, Chronic, mg/l: 1200.0 Summer 1200.0 TDS, mg/l: **Modeling Parameters:** Acute River Width: 50.0% Chronic River Width: 100.0% Antidegradation Level II Review is NOT Required Date: 1/29/2014 Permit Writer: WLA by: WQM Sec. Approval:

TMDL Sec. Approval:

WASTELOAD ANALYSIS [WLA] Addendum: Statement of Basis

29-Jan-14 4:00 PM

Facilities:

**Velvet Mine** 

**UPDES No: UT-UT0025810** 

Discharging to:

unnamed dry wash:Big Indian Wash:Hatch Wash:Kane Creek: Colorado River

#### I. Introduction

Wasteload analyses are performed to determine point source effluent limitations necessary to maintain designated beneficial uses by evaluating projected effects of discharge concentrations on in-stream water quality. The wasteload analysis also takes into account downstream designated uses [R317-2-8, UAC]. Projected concentrations are compared to numeric water quality standards to determine acceptability. The anti-degradation policy and procedures are also considered. The primary in-stream parameters of concern may include metals (as a function of hardness), total dissolved solids (TDS), total residual chlorine (TRC), un-ionized ammonia (as a function of pH and temperature, measured and evaluated interms of total ammonia), and dissolved oxygen.

Mathematical water quality modeling is employed to determine stream quality response to point source discharges. Models aid in the effort of anticipating stream quality at future effluent flows at critical environmental conditions (e.g., low stream flow, high temperature, high pH, etc).

The numeric criteria in this wasteload analysis may always be modified by narrative criteria and other conditions determined by staff of the Division of Water Quality.

#### II. Receiving Water and Stream Classification

unnamed dry wash:Big Indian Wash:Hatch Wash:Kane Creek: Colorado River:

2B, 3C, 4

Antidegradation Review:

Antidegradation Level II Review is NOT Required

#### III. Numeric Stream Standards for Protection of Aquatic Wildlife

Total Ammonia (TNH3)

Varies as a function of Temperature and pH Rebound. See Water Quality Standards

Chronic Total Residual Chlorine (TRC)

0.011 mg/l (4 Day Average) 0.019 mg/l (1 Hour Average)

Chronic Dissolved Oxygen (DO)

5.00 mg/l (30 Day Average) N/A mg/l (7Day Average) 3.00 mg/l (1 Day Average

Maximum Total Dissolved Solids

1200.0 mg/l

#### **Acute and Chronic Heavy Metals (Dissolved)**

	4 Day Average (Chronic)	1 Hour Average (Acute) Standard			
Parameter	Concentration	Load*	Concentration		Load*
Aluminum	87.00 ug/l**	0.363 lbs/day	750.00	ug/l	3.127 lbs/day
Arsenic	190.00 ug/l	0.792 lbs/day	340.00	ug/l	1.418 lbs/day
Cadmium	0.52 ug/l	0.002 lbs/day	5.17	ug/l	0.022 lbs/day
Chromium III	175.79 ug/l	0.733 lbs/day	3677.92	ug/l	15.334 lbs/day
ChromiumVI	11.00 ug/l	0.046 lbs/day	16.00	ug/l	0.067 lbs/day
Copper	19.63 ug/l	0.082 lbs/day	31.79	ug/l	0.133 lbs/day
Iron			1000.00	ug/l	4.169 lbs/day
Lead	9.64 ug/l	0.040 lbs/day	247.26	ug/l	1.031 lbs/day
Mercury	0.0120 ug/l	0.000 lbs/day	2.40	ug/l	0.010 lbs/day
Nickel	108.93 ug/l	0.454 lbs/day	979.80	ug/l	4.085 lbs/day
Selenium	4.60 ug/l	0.019 lbs/day	20.00	ug/l	0.083 lbs/day
Silver	N/A ug/l	N/A lbs/day	16.91	ug/l	0.071 lbs/day
Zinc	250.50 ug/l	1.044 lbs/day	250.50	ug/i	1.044 lbs/day
A A ()	tit t Paul anna				

<sup>\*</sup> Allowed below discharge

Metals Standards Based upon a Hardness of 238.79 mg/l as CaCO3

Organics [Pesticides]						
	4 Day Averag	je (Chroni	ic) Standard	- 1 Hour Ave	rage (Acute	e) Standard
Parameter	Concent	tration	Load*	Concentration		Load*
Aldrin				1.500	ug/l	0.006 lbs/day
Chlordane	0.004	ug/l	0.018 lbs/day	1.200	ug/l	0.005 lbs/day
DDT, DDE	0.001	ug/l	0.004 lbs/day	0.550	ug/l	0.002 lbs/day
Dieldrin	0.002	ug/l	0.008 lbs/day	1.250	ug/l	0.005 lbs/day
Endosulfan	0.056	ug/l	0.236 lbs/day	0.110	ug/l	0.000 lbs/day
Endrin	0.002	ug/l	0.010 lbs/day	0.090	ug/l	0.000 lbs/day
Guthion		_		0.010	ug/l	0.000 lbs/day
Heptachlor	0.004	ug/l	0.016 lbs/day	0.260	ug/l	0,001 lbs/day
Lindane	0.080	ug/l	0.338 lbs/day	1.000	ug/l	0.004 lbs/day
Methoxychlor		-		0.030	ug/l	0.000 lbs/day
Mirex				0.010	ug/l	0.000 lbs/day
Parathion				0.040	ug/l	0.000 lbs/day
PCB's	0.014	ug/l	0.059 lbs/day	2.000	ug/l	0.008 lbs/day
Pentachlorophenol		-	54.900 lbs/day	20.000	ug/l	0.083 lbs/day
Toxephene	0.0002	ua/l	0.001 lbs/day	0.7300	ug/l	0.003 lbs/day

<sup>\*\*</sup>Chronic Aluminum standard applies only to waters with a pH < 7.0 and a Hardness < 50 mg/l as CaCO3

	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard		
	Concentration	Load*	Concentration	Load*	
Arsenic			100.0 ug/l	lbs/day	
Boron			750.0 ug/l	lbs/day	
Cadmium			10.0 ug/l	0.02 lbs/day	
Chromium			100.0 ug/l	lbs/day	
Copper			200.0 ug/l	lbs/day	
Lead			100.0 ug/l	lbs/day	
Selenium			50.0 ug/l	lbs/day	
TDS, Summer			1200.0 mg/l	2.50 tons/day	

### V. Numeric Stream Standards for Protection of Human Health (Class 1C Waters)

4	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard		
Metals	Concentration	Load*	Concentration	Load*	
Arsenic			ug/l	lbs/day	
Barium			ug/l	lbs/day	
Cadmium			ug/l	lbs/day	
Chromium			ug/l	lbs/day	
Lead			ug/l	lbs/day	
Mercury			ug/l	lbs/day	
Selenium			ug/l	lbs/day	
Silver			ug/l	lbs/day	
Fluoride (3)			ug/l	lbs/day	
to			ug/l	lbs/day	
Nitrates as N			ug/l	lbs/day	
Chlorophenoxy Herbicio	des		ġ		
2,4-D	ii.		ug/l	lbs/day	
2,4,5-TP			ug/l	lbs/day	
Endrin			ug/l	lbs/day	
ocyclohexane (Lindane)			ug/l	lbs/day	
Methoxychlor			ug/l	lbs/day	
Toxaphene			ug/l	lbs/day	

### VI. Numeric Stream Standards the Protection of Human Health from Water & Fish Consumption [Toxics]

#### Maximum Conc., ug/l - Acute Standards

	Class 1C			Class 3/	A, 3B
Toxic Organics	[2 Liters/Day for 70 Kg	Person over 70 Yr.]	[6.5 g	for 70 k	(g Person over 70 Yr.]
Acenaphthene	ug/l	lbs/day	2700.0	ug/l	11.40 lbs/day
Acrolein	ug/l	lbs/day	780.0	ug/l	3.29 lbs/day
Acrylonitrile	ug/l	lbs/day	0.7	ug/l	0.00 lbs/day
Benzene	ug/l	lbs/day	71.0	ug/l	0.30 lbs/day
Benzidine	ug/l	lbs/day	0.0	ug/l	0.00 lbs/day
Carbon tetrachloride	ug/i	lbs/day	4.4	ug/i	0.02 lbs/day
Chlorobenzene	ug/l	lbs/day	21000.0	ug/l	88.68 lbs/day
1,2,4-Trichlorobenzene					
Hexachlorobenzene	ug/l	lbs/day	0.0	ug/l	0.00 lbs/day
1,2-Dichloroethane	ug/l	lbs/day	99.0	ug/i	0.42 lbs/day

1,1,1-Trichloroethane						
Hexachioroethane	ug/l	lbs/day	8.9	ug/i	0.04	lbs/day
1,1-Dichloroethane	49/1	ibo, day	0.0	~g/.		
1,1,2-Trichloroethane	ug/l	lbs/day	42.0	ua/l	0.18	lbs/day
1,1,2-Themolocularie	ug/i	lbs/day	11.0			lbs/day
Chloroethane	ugn	iborday	0.0	_		lbs/day
Bis(2-chloroethyl) ether	ug/l	lbs/day	1.4	_		lbs/day
2-Chloroethyl vinyl ether	ug/l	lbs/day	0.0	_		lbs/day
• •	ug/l	lbs/day	4300.0			lbs/day
2-Chloronaphthalene	ug/l	lbs/day	6.5	_		lbs/day
2,4,6-Trichlorophenol	ug/i	ibarday	0.0	_		lbs/day
p-Chloro-m-creșol	ug/l	lbs/day	470.0	_		lbs/day
Chloroform (HM)	_	lbs/day	400.0	_		lbs/day
2-Chlorophenol	ug/l	lbs/day	17000.0	_		lbs/day
1,2-Dichlorobenzene	ug/l	lbs/day	2600.0	_		lbs/day
1,3-Dichlorobenzene	ug/l	•	2600.0	•		lbs/day
1,4-Dichlorobenzene	ug/l	lbs/day	0.1			lbs/day
3,3'-Dichlorobenzidine	ug/l	lbs/day		ug/l		lbs/day
1,1-Dichloroethylene	ug/l	lbs/day				-
1,2-trans-Dichloroethyle	ug/l	ibs/day		ug/l		lbs/day
2,4-Dichlorophenol	ug/l	lbs/day	790.0	_		lbs/day
1,2-Dichloropropane	ug/l	lbs/day		ug/l		lbs/day
1,3-Dichloropropylene	ug/l	lbs/day	1700.0	_		lbs/day
2,4-Dimethylphenol	ug/l	lbs/day	2300.0	_		lbs/day
2,4-Dinitrotoluene	ug/l	lbs/day	9.1	_		lbs/day
2,6-Dinitrotoluene	ug/l	lbs/day	0.0	-		lbs/day
1,2-Diphenylhydrazine	ug/l	lbs/day	0.5	-		lbs/day
Ethylbenzene	ug/l	lbs/day	29000.0		122.47	
Fluoranthene	ug/l	lbs/day	370.0	ug/i	1.50	lbs/day
4-Chlorophenyl phenyl ether						
4-Bromophenyl phenyl ether	Xi.	15 - (-1	470000 0		747.00	م المام المام
Bis(2-chloroisopropyl) e	ug/l	lbs/day	170000.0	_	717.92	_
Bis(2-chloroethoxy) met	ug/l	lbs/day	0.0	_		lbs/day
Methylene chloride (HM	ug/l	lbs/day	1600.0			lbs/day
Methyl chloride (HM)	ug/l	lbs/day		ug/l		lbs/day
Methyl bromide (HM)	ug/l	lbs/day	0.0	_		lbs/day
Bromoform (HM)	ug/l	lbs/day	360.0	_		lbs/day
Dichlorobromomethane	ug/l	lbs/day	22.0	_		lbs/day
Chlorodibromomethane	ug/i	lbs/day	34.0	_		lbs/day
Hexachlorobutadiene(c)	ug/l	lbs/day	50.0	-		lbs/day
Hexachlorocyclopentadi	ug/l	lbs/day	17000.0	•		lbs/day
Isophorone	ug/l	lbs/day	600.0	ug/l	2.53	lbs/day
Naphthalene		lla a <i>l a</i> l au .	4000.0		9.00	lba/day
Nitrobenzene	ug/l	lbs/day	1900.0	_		lbs/day
2-Nitrophenol	ug/l	lbs/day	0.0	_		lbs/day
4-Nitrophenol	ug/l	lbs/day	0.0	_		lbs/day
2,4-Dinitrophenol	ug/l	lbs/day	14000.0	_		lbs/day
4,6-Dinitro-o-cresol	ug/l	lbs/day	765.0	_		lbs/day
N-Nitrosodimethylamine	ug/l	lbs/day	8.1	_		lbs/day
N-Nitrosodiphenylamine	ug/i	lbs/day	16.0	_		lbs/day
N-Nitrosodi-n-propylami	ug/l	lbs/day	1.4	_		lbs/day
Pentachlorophenol	ug/l	lbs/day	8.2	ug/l	0.03	lbs/day

Dhanal	//	lb a falas s	4.65,06	/1	1.04E+04.the/de+
Phenol	ug/l	lbs/day	4.6E+06	_	1.94E+04 lbs/day
Bis(2-ethylhexyl)phthala	ug/l	lbs/day		ug/l	0.02 lbs/day
Butyl benzyl phthalate	ug/l	lbs/day	5200.0		21.96 lbs/day
Di-n-butyl phthalate	ug/l	lbs/day	12000.0	ug/i	50.68 lbs/day
Di-n-octyl phthlate					
Diethyl phthalate	ug/l	lbs/day	120000.0		506.77 lbs/day
Dimethyl phthlate	ug/l	lbs/day	2.9E+06	_	1.22E+04 lbs/day
Benzo(a)anthracene (P/	ug/l	lbs/day	0.0	_	0.00 lbs/day
Benzo(a)pyrene (PAH)	ug/l	lbs/day	0.0	-	0.00 lbs/day
Benzo(b)fluoranthene (F	ug/l	lbs/day	0.0		0.00 lbs/day
Benzo(k)fluoranthene (F	ug/l	lbs/day	0.0		0.00 lbs/day
Chrysene (PAH)	ug/l	lbs/day	0.0	ug/l	0.00 lbs/day
Acenaphthylene (PAH)					
Anthracene (PAH)	ug/l	lbs/day	0.0	ug/l	0.00 lbs/day
Dibenzo(a,h)anthracene	ug/l	lbs/day	0.0	ug/l	0.00 lbs/day
Indeno(1,2,3-cd)pyrene	ug/l	lbs/day	0.0		0.00 lbs/day
Pyrene (PAH)	ug/l	lbs/day		ug/l	46.45 lbs/day
Tetrachloroethylene	ug/l	lbs/day		ug/l	0.04 lbs/day
Toluene	ug/l	lbs/day		ug/l	844.61 lbs/day
Trichloroethylene	ug/l	lbs/day	81.0		0.34 lbs/day
Vinyl chloride	ug/l	lbs/day	525.0	_	2.22 lbs/day
VIII VI CIIIONAE	ug/i	iborday	020.0	ugn	lbs/day
Pesticides					lbs/day
Aldrin	ua/l	lbs/day	0.0	ug/l	0.00 lbs/day
	ug/l	•		_	
Dieldrin	ug/l	lbs/day	0.0	-	0.00 lbs/day
Chlordane	ug/l	lbs/day	0.0	_	0.00 lbs/day
4,4'-DDT	ug/l	lbs/day	0.0	_	0.00 lbs/day
4,4'-DDE	ug/l	lbs/day	0.0		0.00 lbs/day
4,4'-DDD	ug/l	lbs/day	0.0		0.00 lbs/day
alpha-Endosulfan	ug/l	lbs/day	2.0		0.01 lbs/day
beta-Endosulfan	ug/l	lbs/day	2.0		0.01 lbs/day
Endosulfan sulfate	ug/l	lbs/day		ug/l	0.01 lbs/day
Endrin	ug/l	lbs/day		ug/l	0.00 lbs/day
Endrin aldehyde	ug/l	lbs/day	8.0	_	0.00 lbs/day
Heptachlor	ug/l	lbs/day	0.0	ug/l	0.00 lbs/day
Heptachlor epoxide					
PCB's					
PCB 1242 (Arochlor 124	ug/l	lbs/day		ug/l	0.00 lbs/day
PCB-1254 (Arochlor 128	ug/l	lbs/day	0.0	ug/l	0.00 lbs/day
PCB-1221 (Arochlor 122	ug/l	lbs/day		ug/l	0.00 lbs/day
PCB-1232 (Arochlor 123	ug/l	lbs/day	0.0	ug/l	0.00 lbs/day
PCB-1248 (Arochlor 124	ug/l	lbs/day		ug/l	0.00 lbs/day
PCB-1260 (Arochlor 12f	ug/l	ibs/day		ug/l	0.00 lbs/day
PCB-1016 (Arochlor 10°	ug/l	lbs/day		ug/l	0.00 lbs/day
Pesticide					
Toxaphene	ug/l		0.0	ug/l	0.00 lbs/day
,	J		<del>-</del>	J	
Dioxin					
Dioxin (2,3,7,8-TCDD)	ug/l	lbs/day			
,	•	•			

Metals				
Antimony	ug/l	lbs/day		
Arsenic	ug/l	lbs/day	4300.00 ug/l	18.16 lbs/day
Asbestos	ug/l	lbs/day		
Beryllium	_			e
Cadmium				
Chromium (III)				
Chromium (VI)			X.	
Copper				
Cyanide	ug/l	lbs/day	2.2E+05 ug/l	929.07 lbs/day
Lead	ug/l	lbs/day		
Mercury			0.15 ug/l	0.00 lbs/day
Nickel			4600.00 ug/l	19.43 lbs/day
Selenium	ug/l	lbs/day		
Silver	ug/l	lbs/day		
Thallium		-	6.30 ug/l	0.03 lbs/day
Zinc.			_	On.

There are additional standards that apply to this receiving water, but were not considered in this modeling/waste load allocation analysis.

#### VII. Mathematical Modeling of Stream Quality

Model configuration was accomplished utilizing standard modeling procedures. Data points were plotted and coefficients adjusted as required to match observed data as closely as possible.

The modeling approach used in this analysis included one or a combination of the following models.

- (1) The Utah River Model, Utah Division of Water Quality, 1992. Based upon STREAMDO IV (Region VIII) and Supplemental Ammonia Toxicity Models; EPA Region VIII, Sept. 1990 and QUAL2E (EPA, Athens, GA).
- (2) Utah Ammonia/Chlorine Model, Utah Division of Water Quality, 1992.
- (3) AMMTOX Model, University of Colorado, Center of Limnology, and EPA Region 8
- (4) Principles of Surface Water Quality Modeling and Control. Robert V. Thomann, et.al. Harper Collins Publisher, Inc. 1987, pp. 644.

Coefficients used in the model were based, in part, upon the following references:

(1) Rates, Constants, and Kinetics Formulations in Surface Water Quality Modeling. Environmental Research Laboratory, Office of Research and Development, U.S. Environmental Protection Agency, Athens Georgia. EPA/600/3-85/040 June 1985.

(2) Principles of Surface Water Quality Modeling and Control. Robert V. Thomann, et.al. Harper Collins Publisher, Inc. 1987, pp. 644.

#### VIII. Modeling Information

The required information for the model may include the following information for both the upstream conditions at low flow and the effluent conditions:

Flow, Q, (cfs or MGD)

D.O. mg/l

Temperature, Deg. C.

Total Residual Chlorine (TRC), mg/l

pН

Total NH3-N, mg/l

BOD5, mg/l

Total Dissolved Solids (TDS), mg/l

Metals, ug/l

Toxic Organics of Concern, ug/l

#### **Other Conditions**

In addition to the upstream and effluent conditions, the models require a variety of physical and biological coefficients and other technical information. In the process of actually establishing the permit limits for an effluent, values are used based upon the available data, model calibration, literature values, site visits and best professional judgement.

#### **Model Inputs**

The following is upstream and discharge information that was utilized as inputs for the analysis. Dry washes are considered to have an upstream flow equal to the flow of the discharge.

### Current Upstream Information Stream

	Critical Low							
	Flow	Temp.	рН	T-NH3	BOD5	DO	TRC	TDS
	cfs	Deg. C		mg/l as N	mg/l	mg/l	mg/l	mg/l
Summer (Irrig. Season)	0.0	20.0	8.2	0.10	0.50	9.79	0.00	700.0
Fall	0.0	12.0	8.1	0.10	0.50		0.00	700.0
Winter	0.0	4.0	8.0	0.10	0.50	Termina C	0.00	700.0
Spring	0.0	12.0	8.1	0.10	0.50		0.00	700.0
Dissolved Metals		As ug/l	Cd ug/l	Crlil ug/l	CrVI ug/l	Copper ug/l	Fe ug/l	Pb ug/l
All Seasons		0.53*	0.053*	0.53*	2.65*	0.53*	0.83*	0.53*
Dissolved Metals All Seasons	ug/l	Ni ug/l 0.53*	Se ug/l 1.06*	Ag ug/l 0.1*	Zn ug/l 0.053*	Boron ug/l 10.0		* 1/2 MDL
7 0 0 0 0 0 1 1 0	0.0000	3.00	1,00	0.1	5.000	10.0		

#### **Projected Discharge Information**

Season	Flow, MGD	Temp.	TDS mg/l	TDS tons/day
Summer	0.50000	NA	700.00	1.45921
Fall	0.50000	NA		
Winter	0.50000	NA		
Spring	0.50000	NA		

All model numerical inputs, intermediate calculations, outputs and graphs are available for discussion, inspection and copy at the Division of Water Quality.

#### IX. Effluent Limitations

Current State water quality standards are required to be met under a variety of conditions including in-stream flows targeted to the 7-day, 10-year low flow (R317-2-9).

Other conditions used in the modeling effort coincide with the environmental conditions expected at low stream flows.

#### Effluent Limitation for Flow based upon Water Quality Standards

In-stream criteria of downstream segments will be met with an effluent flow maximum value as follows:

Season	Daily Average	)
Summer	0.500 MGD	0.774 cfs
Fall	0.500 MGD	0.774 cfs
Winter	0.500 MGD	0.774 cfs
Spring	0.500 MGD	0.774 cfs

#### Flow Requirement or Loading Requirement

The calculations in this wasteload analysis utilize the maximum effluent discharge flow of 0.5 MGD. If the discharger is allowed to have a flow greater than 0.5 MGD during 7Q10 conditions, and effluent limit concentrations as indicated, then water quality standards will be violated. In order to prevent this from occuring, the permit writers must include the discharge flow limititation as indicated above; or, include loading effluent limits in the permit.

#### Effluent Limitation for Whole Effluent Toxicity (WET) based upon WET Policy

Effluent Toxicity will not occur in downstream segements if the values below are met.

WET Requirements	LC50 >	EOP Effluent	[Acute]
	IC25 >	98.7% Effluent	[Chronic]

### Effluent Limitation for Biological Oxygen Demand (BOD) based upon Water Quality Standards or Regulations

In-stream criteria of downstream segments for Dissolved Oxygen will be met with an effluent BOD limitation as follows:

Season	Concentration	
Summer	25.0 mg/l as BOD5	104.2 lbs/day
Fall	25.0 mg/l as BOD5	104.2 lbs/day
Winter	25.0 mg/l as BOD5	104.2 lbs/day
Spring	25.0 mg/l as BOD5	104.2 lbs/day

#### Effluent Limitation for Dissolved Oxygen (DO) based upon Water Quality Standards

In-stream criteria of downstream segments for Dissolved Oxygen will be met with an effluent D.O. limitation as follows:

Season	Concentration
Summer	5.00
Fall	5.00
Winter	5.00
Spring	5.00

#### Effluent Limitation for Total Ammonia based upon Water Quality Standards

In-stream criteria of downstream segments for Total Ammonia will be met with an effluent limitation (expressed as Total Ammonia as N) as follows:

Seas	on				
	Concentr	ation		Load	d
Summer	4 Day Avg Chronic	8.2	mg/l as N	34.0	lbs/day
	1 Hour Avg Acute	64.5	mg/l as N	268.8	lbs/day
Fall	4 Day Avg Chronic	8.2	mg/l as N	34.0	lbs/day
	1 Hour Avg Acute	64.5	mg/l as N	268.8	lbs/day
Winter	4 Day Avg Chronic	8.2	mg/l as N	34.0	lbs/day
	1 Hour Avg Acute	64.5	mg/l as N	268.8	lbs/day
Spring	4 Day Avg Chronic	8.2	mg/l as N	34.0	lbs/day
	1 Hour Avg Acute	64.5	mg/l as N	268.8	lbs/day

Acute limit calculated with an Acute Zone of Initial Dilution (ZID) to be equal to 100.%.

### Effluent Limitation for Total Residual Chlorine based upon Water Quality Standards

In-stream criteria of downstream segments for Total Residual Chlorine will be met with an effluent limitation as follows:

Seas	on	Concentr	ation	Loa	ıd
Summer	4 Day Avg Chronic	0.011	mg/l	0.05	lbs/day
	1 Hour Avg Acute	0.019	mg/l	0.08	lbs/day
Fall	4 Day Avg Chronic	0.011	mg/l	0.05	lbs/day
	1 Hour Avg Acute	0.019	mg/l	0.08	lbs/day
Winter	4 Day Avg Chronic	0.011	mg/l	0.05	lbs/day
	1 Hour Avg Acute	0.019	mg/l	0.08	lbs/day
Spring	4 Day Avg Chronic	0.011	mg/l	0.00	lbs/day
	1 Hour Avg Acute	0.019	mg/l	0.00	lbs/day

### Effluent Limitations for Total Dissolved Solids based upon Water Quality Standards

Seas	on	Concentra	ation	Load	i
Summer Fall Winter Spring	Maximum, Acute Maximum, Acute Maximum, Acute 4 Day Avg Chronic	1206.5 1206.5 1206.5 1206.5	mg/l mg/l mg/l mg/l	2.51 2.51 2.51 2.51	tons/day tons/day tons/day tons/day
Colorado S	alinity Forum Limits	Determine	d by Permit	ting Section	

## Effluent Limitations for Total Recoverable Metals based upon Water Quality Standards

In-stream criteria of downstream segments for Dissolved Metals will be met with an effluent limitation as follows (based upon a hardness of 238.79 mg/l):

		4 Day Ave	rage	1 Hour A	verage	
	Concen	tration	Load	Concentration		Load
Aluminum	N/A		N/A	759.7	ug/l	3.2 lbs/day
Arsenic	192.45	ug/l	0.5 lbs/day	344.4	ug/l	1.4 lbs/day
Cadmium	0.52	_	0.0 lbs/day	5.2	ug/l	0.0 lbs/day
Chromium III		ug/l	0.5 lbs/day	3,725.5	ug/l	15.5 lbs/day
Chromium VI		_	0.0 lbs/day	16.2	ug/l	0.1 lbs/day
Copper	19.87	ug/l	0.1 lbs/day	32.2	ug/l	0.1 lbs/day
Iron	N/A		N/A	1,012.9	ug/l	4.2 lbs/day
Lead	9.75	ug/l	0.0 lbs/day	250.4	ug/l	1.0 lbs/day
Mercury	0.01	ug/l	0.0 lbs/day	2.4	ug/l	0.0 lbs/day
Nickel	110.33	•	0.3 lbs/day	992.5	ug/l	4.1 lbs/day
Selenium	4.64	ug/l	0.0 lbs/day	20.2	ug/l	0.1 lbs/day
Silver		_	N/A lbs/day	17.1	ug/l	0.1 lbs/day

Zinc	253.74 ug/l	0.7 lbs/day	253.7	ug/l	1.1 lbs/day
Cyanide	5.27 ug/l	0.0 lbs/day	22.3	ug/l	0.1 lbs/day

## Effluent Limitations for Heat/Temperature based upon Water Quality Standards

Summer	22.0 Deg. C.	71.6 Deg. F
Fall	14.0 Deg. C.	57.2 Deg. F
Winter	6.0 Deg. C.	42.8 Deg. F
Spring	14.0 Deg. C.	57.2 Deg. F

## Effluent Limitations for Organics [Pesticides] Based upon Water Quality Standards

In-stream criteria of downstream segments for Organics [Pesticides] will be met with an effluent limit as follows:

	4 Day Ave	erage	1 Hour A	verage	
	Concentration	Load	Concentration		Load
Aldrin			1.5E+00	ug/l	9.67E-03 lbs/day
Chlordane	4.30E-03 ug/l	1.79E-02 lbs/day	1.2E+00	ug/l	7.74E-03 lbs/day
DDT, DDE	1.00E-03 ug/l	4.17E-03 lbs/day	5.5E-01	ug/l	3.55E-03 lbs/day
Dieldrin	1.90E-03 ug/l	7.92E-03 lbs/day	1.3E+00	ug/l	8.06E-03 lbs/day
Endosulfan	5.60E-02 ug/l	2.33E-01 lbs/day	1.1E-01	ug/l	7.09E-04 lbs/day
Endrin	2.30E-03 ug/l	9.59E-03 lbs/day	9.0E-02	ug/l	5.80E-04 lbs/day
Guthion	0.00E+00 ug/l	0.00E+00 lbs/day	1.0E-02	ug/l	6.45E-05 lbs/day
Heptachlor	3.80E-03 ug/l	1.58E-02 lbs/day	2.6E-01	ug/l	1.68E-03 lbs/day
Lindane	8.00E-02 ug/l	3.34E-01 lbs/day	1.0E+00	ug/l	6.45E-03 lbs/day
Methoxychlor	0.00E+00 ug/l	0.00E+00 lbs/day	3.0E-02	ug/l	1.93E-04 lbs/day
Mirex	0.00E+00 ug/l	0.00E+00 lbs/day	1.0E-02	ug/l	6.45E-05 lbs/day
Parathion	0.00E+00 ug/l	0.00E+00 lbs/day	4.0E-02	ug/l	2.58E-04 lbs/day
PCB's	1.40E-02 ug/l	5.84E-02 lbs/day	2.0E+00	ug/l	1.29E-02 lbs/day
Pentachlorophenol	1.30E+01 ug/l	5.42E+01 lbs/day	2.0E+01	ug/l	1.29E-01 lbs/day
Toxephene	2.00E-04 ug/l	8.34E-04 lbs/day	7.3E-01	ug/l	4.71E-03 lbs/day

### Effluent Targets for Pollution Indicators Based upon Water Quality Standards

In-stream criteria of downstream segments for Pollution Indicators will be met with an effluent limit as follows:

	1 Hour Average		
	Concentration	Loading	
Gross Beta (pCi/l)	50.0 pCi/L		
BOD (mg/l)	5.0 mg/l	20.8 lbs/day	
Nitrates as N	4.0 mg/l	16.7 lbs/day	
Total Phosphorus as P	0.05 mg/l	0.2 lbs/day	
Total Suspended Solids	90.0 mg/l	375.2 lbs/day	

Note: Pollution indicator targets are for information purposes only.

## Effluent Limitations for Protection of Human Health [Toxics Rule] Based upon Water Quality Standards (Most stringent of 1C or 3A & 3B as appropriate.)

In-stream criteria of downstream segments for Protection of Human Health [Toxics] will be met with an effluent limit as follows:

	Maximum Concentration		
	Concentration	Load	
Toxic Organics			
Acenaphthene	2.73E+03 ug/l	1.14E+01 lbs/day	
Acrolein	7.90E+02 ug/l	3.29E+00 lbs/day	
Acrylonitrile	6.69E-01 ug/l	2.79E-03 lbs/day	
Benzene	7.19E+01 ug/l	3.00E-01 lbs/day	
Benzidine	ug/l	lbs/day	
Carbon tetrachloride	4.46E+00 ug/l	1.86E-02 lbs/day	
Chlorobenzene	2.13E+04 ug/l	8.87E+01 lbs/day	
1,2,4-Trichlorobenzene			
Hexachlorobenzene	7.80E-04 ug/l	3.25E-06 lbs/day	
1,2-Dichloroethane	1.00E+02 ug/l	4.18E-01 lbs/day	
1,1,1-Trichloroethane			
Hexachloroethane	9.02E+00 ug/l	3.76E-02 lbs/day	
1,1-Dichloroethane			
1,1,2-Trichloroethane	4.25E+01 ug/l	1.77E-01 lbs/day	
1,1,2,2-Tetrachloroethane	1.11E+01 ug/l	4.65E-02 lbs/day	
Chloroethane			
Bis(2-chloroethyl) ether	1.42E+00 ug/l	5.91E-03 lbs/day	
2-Chloroethyl vinyl ether			
2-Chloronaphthalene	4.36E+03 ug/l	1.82E+01 lbs/day	
2,4,6-Trichlorophenol	6.58E+00 ug/l	2.74E-02 lbs/day	
p-Chloro-m-cresol			
Chloroform (HM)	4.76E+02 ug/l	1.98E+00 lbs/day	
2-Chlorophenol	4.05E+02 ug/l	1.69E+00 lbs/day	
1,2-Dichlorobenzene	1.72E+04 ug/l	7.18E+01 lbs/day	
1,3-Dichlorobenzene	2.63E+03 ug/l	1.10E+01 lbs/day	

1,4-Dichlorobenzene 3,3'-Dichlorobenzidine	2.63E+03 ug/l 7.80E-02 ug/l	1.10E+01 lbs/day - 3.25E-04 lbs/day
1,1-Dichloroethylene 1,2-trans-Dichloroethylene1	3.24E+00 ug/l	1.35E-02 lbs/day
2,4-Dichlorophenol	8.00E+02 ug/l	3.34E+00 lbs/day
1,2-Dichloropropane	3.95E+01 ug/l	1.65E-01 lbs/day
1,3-Dichloropropylene	1.72E+03 ug/l	7.18E+00 lbs/day
2,4-Dimethylphenol	2.33E+03 ug/l	9.71E+00 lbs/day
2,4-Dinitrotoluene	9.22E+00 ug/l	3.84E-02 lbs/day
2,6-Dinitrotoluene		
1,2-Diphenylhydrazine	5.47E-01 ug/l	2.28E-03 lbs/day
Ethylbenzene	2.94E+04 ug/l	1.22E+02 lbs/day
Fluoranthene	3.75E+02 ug/l	1.56E+00 lbs/day
4-Chlorophenyl phenyl ether		
4-Bromophenyl phenyl ether		
Bis(2-chloroisopropyl) ether	1.72E+05 ug/l	7.18E+02 lbs/day
Bis(2-chloroethoxy) methane		
Methylene chloride (HM)	1.62E+03 ug/l	6.76E+00 lbs/day
Methyl chloride (HM)		
Methyl bromide (HM)		
Bromoform (HM)	3.65E+02 ug/l	1.52E+00 lbs/day
Dichlorobromomethane(HM)	2.23E+01 ug/l	9.29E-02 lbs/day
Chlorodibromomethane (HM)	3.44E+01 ug/l	1.44E-01 lbs/day
Hexachlorocyclopentadiene	1.72E+04 ug/l	7.18E+01 lbs/day
Isophorone	6.08E+02 ug/l	2.53E+00 lbs/day
Naphthalene	4.00=.00=#	0.005.00 #1
Nitrobenzene	1.92E+03 ug/l	8.02E+00 lbs/day
2-Nitrophenol		
4-Nitrophenol	4.405.04	FOAFIOA Iba/day
2,4-Dinitrophenol	1.42E+04 ug/l	5.91E+01 lbs/day
4,6-Dinitro-o-cresol	7.75E+02 ug/l	3.23E+00 lbs/day
N-Nitrosodimethylamine	8.20E+00 ug/l 1.62E+01 ug/l	3.42E-02 lbs/day
N-Nitrosodiphenylamine	1.42E+00 ug/l	6.76E-02 lbs/day 5.91E-03 lbs/day
N-Nitrosodi-n-propylamine	8.31E+00 ug/l	3.46E-02 lbs/day
Pentachlorophenol Phenol	4.66E+06 ug/l	1.94E+04 lbs/day
Bis(2-ethylhexyl)phthalate	5.98E+00 ug/l	2.49E-02 lbs/day
Butyl benzyl phthalate	5.27E+03 ug/l	2.20E+01 lbs/day
Di-n-butyl phthalate	1.22E+04 ug/l	5.07E+01 lbs/day
Di-n-octyl phthlate	1.222 · 04 · ug/i	O.O. E. O. I Iborday
Diethyl phthalate	1.22E+05 ug/l	5.07E+02 lbs/day
Dimethyl phthlate	2.94E+06 ug/l	1.22E+04 lbs/day
Benzo(a)anthracene (PAH)	3.14E-02 ug/l	1.31E-04 lbs/day
Benzo(a)pyrene (PAH)	3.14E-02 ug/l	1.31E-04 lbs/day
Benzo(b)fluoranthene (PAH)	3.14E-02 ug/l	1.31E-04 lbs/day
Benzo(k)fluoranthene (PAH)	3.14E-02 ug/l	1.31E-04 lbs/day
Chrysene (PAH)	3.14E-02 ug/l	1.31E-04 lbs/day
Acenaphthylene (PAH)		
Anthracene (PAH)		
Dibenzo(a,h)anthracene (PAH)	3.14E-02 ug/l	1.31E-04 lbs/day
Indeno(1,2,3-cd)pyrene (PAH)	3.14E-02 ug/l	1.31E-04 lbs/day

Pyrene (PAH) Tetrachloroethylene Toluene Trichloroethylene Vinyl chloride	1.11E+04 ug/l 9.02E+00 ug/l 2.03E+05 ug/l 8.20E+01 ug/l 5.32E+02 ug/l	4.65E+01 lbs/day 3.76E-02 lbs/day 8.45E+02 lbs/day 3.42E-01 lbs/day 2.22E+00 lbs/day
Pesticides Aldrin Dieldrin Chlordane 4,4'-DDT 4,4'-DDE 4,4'-DDD alpha-Endosulfan beta-Endosulfan Endosulfan sulfate Endrin Endrin aldehyde Heptachlor Heptachlor epoxide	1.42E-04 ug/l 1.42E-04 ug/l 5.98E-04 ug/l 5.98E-04 ug/l 5.98E-04 ug/l 8.51E-04 ug/l 2.03E+00 ug/l 2.03E+00 ug/l 2.03E+00 ug/l 8.20E-01 ug/l 8.20E-01 ug/l 2.13E-04 ug/l	5.91E-07 lbs/day 5.91E-07 lbs/day 2.49E-06 lbs/day 2.49E-06 lbs/day 3.55E-06 lbs/day 8.45E-03 lbs/day 8.45E-03 lbs/day 3.42E-03 lbs/day 3.42E-03 lbs/day 8.87E-07 lbs/day
PCB's PCB 1242 (Arochlor 1242) PCB-1254 (Arochlor 1254) PCB-1221 (Arochlor 1221) PCB-1232 (Arochlor 1232) PCB-1248 (Arochlor 1248) PCB-1260 (Arochlor 1260) PCB-1016 (Arochlor 1016)  Pesticide Toxaphene	4.56E-05 ug/l 4.56E-05 ug/l 4.56E-05 ug/l 4.56E-05 ug/l 4.56E-05 ug/l 4.56E-05 ug/l 7.60E-04 ug/l	1.90E-07 lbs/day 1.90E-07 lbs/day 1.90E-07 lbs/day 1.90E-07 lbs/day 1.90E-07 lbs/day 1.90E-07 lbs/day 1.90E-07 lbs/day
Metals Antimony Arsenic Asbestos Beryllium Cadmium Chromium (III) Chromium (VI)	ug/l ug/l ug/l	lbs/day lbs/day lbs/day
Copper Cyanide Lead Mercury Nickel	ug/l ug/l ug/l ug/l	lbs/day lbs/day lbs/day lbs/day
Selenium Silver Thallium Zinc	ug/l	lbs/day

Dioxin

Dioxin (2,3,7,8-TCDD)

1.42E-08 ug/l

5.91E-11 lbs/day

#### Metals Effluent Limitations for Protection of All Beneficial Uses Based upon Water Quality Standards and Toxics Rule

	Class 4 Acute Agricultural ug/l	Class 3 Acute Aquatic Wildlife ug/l	Acute Toxics Drinking Water Source ug/l	Acute Toxics Wildlife ug/l	1C Acute Health Criteria ug/l	Acute Most Stringent ug/l	Class 3 Chronic Aquatic Wildlife ug/l
Aluminum		759.7		42EE G		759.7	N/A
Antimony	404.0	244.4		4355.6	0.0	4355.6 101.3	192.4
Arsenic Barium Beryllium	101.3	344.4			0.0	0.0	192.4
Cadmium	10.1	5.2			0.0	5.2	0.5
Chromium (III)	,	3725.5			0.0	3725.5	178.1
Chromium (VI)	101.3	16.2			0.0	16.16	11.09
Соррег	202.6	32.2				32.2	19.9
Cyanide		22.3	222844.2			22.3	5.3
Iron		1012.9				1012.9	
Lead	101.3	250.4			0.0	101.3	9.7
Mercury		2.43		0.15	0.0	0.15	0.012
Nickel		992.5		4659.5		992.5	110.3
Selenium	50.6	20.2			0.0	20.2	4.6
Silver		17.1			0.0	17.1	
Thallium				6.4		6.4	
Zinc		253.7				253.7	253.7
Boron	759.7					759.7	

#### Summary Effluent Limitations for Metals [Wasteload Allocation, TMDL]

[If Acute is more stringent than Chronic, then the Chronic takes on the Acute value.]

	WLA Acute ug/l	WLA Chroni ug/l	c
Aluminum	759.7	N/A	
Antimony	4355.59		
Arsenic	101.3	192.4	Acute Controls
Asbestos	0.00E+00		
Barium			
Beryllium			
Cadmium	5.2	0.5	
Chromium (III)	3725.5	178	
Chromium (VI)	16.2	11.1	
Copper	32.2	19.9	

Cyanide	22.3	5.3
Iron	1012.9	
Lead	101.3	9.7
Mercury	0.152	0.012
Nickel	992.5	110
Selenium	20.2	4.6
Silver	17.1	N/A
Thallium	6.4	
Zinc	253.7	253.7
Boron	759.70	

Other Effluent Limitations are based upon R317-1.

E. coli

126.0 organisms per 100 ml

#### X. Antidegradation Considerations

The Utah Antidegradation Policy allows for degradation of existing quality where it is determined that such lowering of water quality is necessary to accommodate important economic or social development in the area in which the waters are protected [R317-2-3]. It has been determined that certain chemical parameters introduced by this discharge will cause an increase of the concentration of said parameters in the receiving waters. Under no conditions will the increase in concentration be allowed to interfere with existing instream water uses.

The antidegradation rules and procedures allow for modification of effluent limits less than those based strictly upon mass balance equations utilizing 100% of the assimilative capacity of the receiving water. Additional factors include considerations for "Blue-ribbon" fisheries, special recreational areas, threatened and endangered species, and drinking water sources.

An Antidegradation Level I Review was conducted on this discharge and its effect on the receiving water. Based upon that review, it has been determined that an Antidegradation Level II Review is NOT Required

#### XI. Colorado River Salinity Forum Considerations

Discharges in the Colorado River Basin are required to have their discharge at a TDS loading of less than 1.00 tons/day unless certain exemptions apply. Refer to the Forum's Guidelines for additional information allowing for an exceedence of this value.

#### XII. Summary Comments

The mathematical modeling and best professional judgement indicate that violations of receiving water beneficial uses with their associated water quality standards, including important downstream segments, will not occur for the evaluated parameters of concern as discussed above if the effluent limitations indicated above are met.

#### XIII. Notice of UPDES Requirement

This Addendum to the Statement of Basis does not authorize any entity or party to discharge to the waters of the State of Utah. That authority is granted through a UPDES permit issued by the Utah Division of Water Quality. The numbers presented here may be changed as a function of other factors. Dischargers are strongly urged to contact the Permits Section for further information. Permit writers may utilize other information to adjust these limits and/or to determine other limits based upon best available technology and other considerations provided that the values in this wasteload analysis [TMDL] are not compromised. See special provisions in Utah Water Quality Standards for adjustments in the Total Dissolved Solids values based upon background concentration.

Utah Division of Water Quality 801-538-6052 File Name:

#### **APPENDIX - Coefficients and Other Model Information**

CBOD	CBOD	CBOD	REAER.	REAER.	REAER.	NBOD	NBOD
Coeff.	Coeff.	Coeff.	Coeff.	Coeff.	Coeff.	Coeff.	Coeff.
(Kd)20	FORCED	(Ka)T	(Ka)20	FORCED	(Ka)T	(Kn)20	(Kn)T
1/day	(Kd)/day	1/day	(Ka)/day	1/day	1/day	1/day	1/day
2.000	0.000	0.875	590.113	0.000	385.067	0.250	0.063
Open	Open	NH3	NH3	NO2+NO3	NO2+NO3	TRC	TRC
Coeff.	Coeff.	LOSS		LOSS		Decay	
(K4)20	(K4)T	(K5)20	(K5)T	(K6)20	(K6)T	K(CI)20	K(CI)(T)
1/day	1/day	■ 1/day	1/day	1/day	1/day	1/day	1/day
0.000	0.000	4.000	1.750	0.000	0.000	32.000	11.211
BENTHIC	BENTHIC						
DEMAND	DEMAND						
(SOD)20	(SOD)T						
gm/m2/day	gm/m2/day						
1.000	0.322						
124	K0	К3	K4	K5	K6	K(CI)	S
K1	K2			NH3 Loss	NO2+3	K(CI) TRC	Benthic
CBOD	Reaer.	NH3	Open				
{theta}	{theta}	{theta}	{theta}		{theta}	{theta}	{theta}
1.0	1.0	1.1	1.0	1.0	1.0	1.1	1.1

×				
			::	